AN OVERVIEW OF GPS AUGMENTATION SYSTEMS

M. G. Petovello and Gerard Lachapelle
Department of Geomatics Engineering
The University of Calgary
Calgary, Alberta, Canada

Patrick C. Fenton
NovAtel, Inc.
T3K3V6 Calgary, Alberta, Canada

Abstract

The mature satellite-based navigation systems that are now available (e.g., GPS) have provided adequate positioning capability to users. However, their very success has been a driving force to increase accuracy, availability, reliability, and integrity requirements. As a result, several satellite augmentation systems have been or are in the process of being designed, developed, and/or tested in order to meet the ever-demanding requirements. This paper will provide a summary of the current possibilities to improve GPS performance, namely the impact of the GPS modernization program itself, augmentation with the satellite-based GLONASS, WAAS, MSAS, and EGNOS systems, and augmentation with on-board aiding; e.g., barometers and clocks. Performances are discussed as a function of user mask angle. The impact of combined GPS/GALILEO is briefly addressed.

WHY AUGMENTATION?

- Standalone GPS is not adequate for many applications in terms of [1]:
  - *Integrity* - the ability to protect the user from inaccurate information in a timely manner
  - *Accuracy* - the difference between measured and true positions of a vehicle at any given time
  - *Continuity* - the ability to complete an operation without triggering an alarm
  - *Availability* - the ability to be used by the user whenever it is needed

[1] - Loh, R., et al., (1995) "The U.S. Wide-Area Augmentation System (WAAS)", Navigation: Journal of The Institute of Navigation, Vol 42, No 3, Fall 1995, pp. 435-465.

Report Documentation Page

Form Approved
OMB No. 0704-0188

1. REPORT DATE **DEC 1999**	2. REPORT TYPE	3. DATES COVERED **00-00-1999 to 00-00-1999**
4. TITLE AND SUBTITLE **An Overview of GPS Augmentation Systems**		5a. CONTRACT NUMBER 5b. GRANT NUMBER 5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)		5d. PROJECT NUMBER 5e. TASK NUMBER 5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) **The University of Calgary,Department of Geomatics Engineering,Calgary, Alberta, Canada,**		8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S) 11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

13. SUPPLEMENTARY NOTES
See also ADM001481. 31st Annual Precise Time and Time Interval (PTTI) Planning Meeting, 7-9 December 1999, Dana Point, CA

14. ABSTRACT
see report

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT **unclassified**	b. ABSTRACT **unclassified**	c. THIS PAGE **unclassified**	**Same as Report (SAR)**	**13**	

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std Z39-18

"AUGMENTATION" OPTIONS

- Receiver algorithms (RAIM)
- Additional sensors
- Extra systems
  - GLONASS
  - GNSS2 - Galileo
- GPS Modernization
- Local Area Augmentation Systems (LAAS)
- Wide Area Augmentation Systems (WAAS)
  - EGNOS, US WAAS, MSAS

RECEIVER ALGORITHMS

- Receiver Autonomous Integrity Monitoring (RAIM)
- Fault Detection and Exclusion (FDE)
- Simple implementations can produce a significant reliability improvements [e.g., 2]
- Requires five or more satellites
  - Reduces/limits availability

[2] - Ryan, S., J. Stephen and G. Lachapelle, (1999) "Testing and Analysis of Reliability Measures for GNSS Receivers in the Marine Environment", Proceedings of the ION NTM-99, The Institute of Navigation, Alexandria, VA., pp. 505-514.

Example of RAIM/FDE



[2] - Ryan, S., J. Stephen and G. Lachapelle, (1999) "Testing and Analysis of Reliability Measures for GNSS Receivers in the Marine Environment", Proceedings of the ION NTM-99, The Institute of Navigation, Alexandria, VA., pp. 505-514.

ADDITIONAL ON-BOARD SENSORS

- Use of additional or complementary on-board sensors to monitor and/or augment GPS
  - Altimeter
  - Precise clock
  - Rate gyro
  - Compass
  - INS
- Vehicle Autonomous Integrity Monitoring (VAIM)
  - All on-board sensors contribute to navigation reliability

GLONASS

- Constellation of 10 operational satellites (as of November 30, 1999)
- Signal transmit on two frequencies
- No intentional degradation of ranging signal
- Large improvement in availability and reliability when combined with GPS
- Future of the system is uncertain

GNSS2 – GALILEO

- New satellite system conceived by the European Community (EC)
- Completion planned for 2008
- Constellation of 24+ satellites
  - Increased availability and reliability over GPS only
- Three to four carrier frequencies
  - Increased reliability

GPS MODERNIZATION

- Currently, L2 is not in a protected RF band
  - 3rd frequency needed for safety-of-life
- 2nd and 3rd civil frequencies confirmed
  - 1227.60 MHz (L2)
  - 1176.45 MHz (ARNS band), first launch 2005
- Higher power levels
- More robust code-modulation techniques



[3] - McDonald, K., (1999) "Opportunity Knocks: Will GPS Modernization Open Doors?", GPS World, Vol 10, No 9, September 1999, Advanstar Communications, pp. 36-46.

FAA SPECIFICATIONS

Requirement	Category I	Category II	Category III
Vertical Position Accuracy **	4.0 m	2.5 m	2.5 m
Integrity	4e-8 / approach	4e-8 / approach	1e-9 / approach
Time-to-Alert	6 seconds	2 seconds	2 seconds
Vertical Alarm Limit	10 m	5 m	5 m
Continuity	1e-5 / approach	1e-5 / approach	1e-7 / 30s

WAAS

LAAS

[4] - Federal Aviation Administration, (1999) "Local Area Augmentation System (LAAS) Update" Available at URL: http://gps.faa.gov/Library/Documents/documents.htm#laas

WIDE AREA AUGMENTATION SYSTEMS (WAAS)

Phases of Flight		Integrity	Availability	Accuracy
En Route	Oceanic	GPS with RAIM		
	Domestic	WAAS		
Approach & Landing	Non-Precision Approaches			
	Category I Precision Approach	WAAS and LAAS		
	Category II/III Precision Approach	LAAS		
Surface	Ground Movement			

- Major push from aviation community
- Designed to allow sole use of GPS for all phases of flight through Category I precision approach

[5] - Hanlon, D. and K. Sandhoo, (1997) "FAA Satellite Navigation Program Overview", Proceedings of the ION Annual Meeting, The Institute of Navigation, Alexandria, VA., pp. 49-56.

- Three basic functions of a WAAS
  - Ranging
    - Provide additional ranging signals to improve availability, typically via geo-synchronous satellites
  - Integrity Channel
    - Provide transmission of GPS and integrity data to navigators
  - Wide Area Differential (WAD)
    - Provide differential correction data to users to improve accuracy
      - Satellite orbit and clock errors
      - Differential range corrections
      - Ionospheric grid computation

US WAAS

- Wide area Reference Station (WRS)
  - Collect and process data
- Wide area Master Station (WMS)
  - Compute all corrections to be received by users
- Ground Earth Station (GES)
  - Transmission to geo-synchronous satellites
- Communication Satellites (GEO)
  - Broadcast corrections and ranging signal

US WAAS Concept



Picture taken from URL - http://www.isicns.com/GPSWSLS.HTM#WAAS

EUROPEAN WAAS – EGNOS

- European Geostationary Navigation Overlay System (EGNOS)
- Similar to US WAAS but includes GLONASS satellite corrections as well



■ EGNOS Service Volume

▨ INMARSAT Coverage

- **Ground Segment**
  - **Ranging and Integrity Monitoring Stations (RIMS)**
    - **Collect range measurements and send them to the MCC**
  - **Master Control Centre (MCC)**
    - **Computation, distribution, validation, and transmission of data**
    - **Manage and control entire EGNOS system**
  - **Geostationary Reference Station (GRS)**
    - **Monitor geostationary satellites**
    - **Geostationary orbit determination**
  - **Navigation Land Earth Station (NLES)**
    - **Generate GPS-like signal centered on GPS L1 (1575.42 MHz) modulated with C/A code and navigation message (correction data)**
    - **Broadcast through geostationary satellites**
    - **Closed-loop control to maintain EGNOS system time**

[6] - Loddo, et al., "EGONS, the European Regional Augmentation to GPS and GLONASS", The Proceedings of ION GPS-99, The Institute of Navigation, Alexandria, VA., pp. 1143-1150.

European WAAS - EGNOS

- Space Segment
  - GPS satellites
  - GLONASS satellites
  - INMARSAT III satellites for data transmission and ranging function (GEO)
- User segment
  - Signal in Space (SIS)
  - Receiver capable of receiving and decoding the GEO broadcast message



JAPANESE WAAS - MSAS

- MTSAT (Multi-Functional Transport SATellite) based Satellite Augmentation System (MSAS)
- Similar to EGNOS system (GPS and GLONASS)
- Limited geographical extent may lead to problems with orbit determination
  - Dynamic approach to orbit determination
  - Orbital relaxation approach

- Ground Segment
  - Ground Monitor Stations (GMS)
    - Collect range measurements and send them to the MCS
  - Monitor and Ranging Stations (MRS)
    - Receive GPS/MTSAT signals and collect range data
  - Master Control Stations (MCS)
    - Monitor and control system
    - Calculate MTSAT orbit, ionospheric delay, and correction data
    - Determine system integrity
    - Collect range data (GPS and MTSAT)
    - Send data to NES for uplink to MTSAT for broadcast
  - Navigation Earth Stations (NES)
    - Uplinks data from MCS to MTSAT for broadcast



- Two Aeronautical Satellite Centers which include:
  - MRS's
  - 8 GMS's
  - 1 MCS's
- Launch of MTSAT satellite failed (November, 1999)
  - Rocket booster failure

LOCAL AREA AUGMENTATION SYSTEMS (LAAS)

- FAA initiative to use GPS for all categories of precise landing, including CAT III
- Major differences from WAAS include
  - Limited range (~30 nm)
  - Limited number of base stations (~4)
  - Single differential correction to account for all errors
  - Smoothed-code or carrier-phase approaches are necessary
  - Ranging improvement through pseudolites

LAAS Concept



[4] - Federal Aviation Administration, (1999) "Local Area Augmentation System (LAAS) Update" Available at URL: http://gps.faa.gov/Library/Documents/documents.htm#laas

WAAS RESULTS



MI - Misleading Information

HMI - Hazardously Misleading Information

HAL - Horizontal Alarm Limit



MI - Misleading Information

HMI - Hazardously Misleading Information

IPV - Instrument Precision with Vertical Guidance

VAL - Vertical Alarm Limit

Taken from URL - http://www.stanford.edu/group/GPS/Projects/WAAS/metrics.html

CONCLUSIONS

- SPS GPS is not robust enough for all applications
- Augmentation by WAAS, EGNOS, and MSAS will provide a true GNSS with high integrity, accuracy, and availability

Questions and Answers

MARC WEISS (NIST): I assume, when you showed the improvement with WAAS over the accuracy without WAAS, that was with SA turned on.

PATRICK FENTON (NovAtel): SA was on in both cases, yes.

WEISS: So, with SA turned off –

FENTON: WAAS not only helps with a clock, but is also an orbit computation. With SA off, you'd be probably sitting around 3 to 5 meters just with the orbit uncertainties where WAAS is also going to correct the orbit.

WEISS: So it's at a factor of two, with SA turned off, in improvement?

FENTON: Yes, I would guess that.

DAVID ALLAN (Allan's Time): How do the errors scale with the change in SA level? The current SA level is a peacetime level. Should that increase, which it could, how do the errors go with that level?

FENTON: Well, I think there's a specification for that in the Raytheon system. I might defer to the Raytheon folks next. But it wouldn't be linear because they don't actually broadcast a range rate. They broadcast SA corrections on something like a 6-second time basis, and you have to extrapolate through them. So it would increase linearly with increase of SA. I don't have a good number for that.